

## GE Rod end GE15-UK-DUNLOP - GE15-UK-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge15-uk-dunlop>

SPHERICAL BEARINGS

**GE UK SERIES**

**Description:**  
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.  
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.  
Seals: Polyurethane.

<p><b>Features</b></p> <ul style="list-style-type: none"> <li>Metric bore sizes</li> <li>Low friction</li> <li>High shock loads</li> <li>Extended wear life</li> <li>No maintenance</li> </ul>	<p><b>Possible Applications</b></p> <ul style="list-style-type: none"> <li>Medium-heavy industrial mechanical applications</li> <li>Construction equipment</li> <li>Agricultural equipment</li> <li>Recreational vehicles</li> <li>High precision motion control</li> </ul>	<p><b>Temperature Range</b></p> <p>-200°C to +260°C</p> <p><b>Specification</b></p> <p>ELV &amp; RoHS compliant</p>
--	---	---

Outer Ring: Bearing Steel 100Cr6, Case Hardened      Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Temperature PTFE Composite

### PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	5059161173240
Inside diameter	15 mm
Outside diameter	26 mm
Thickness	12 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE