

SI Rod end FSX-M14-DUNLOP - FSX-M14-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/fsx-m14-dunlop>

FEMALE ROD ENDS



DUNLOP
FSX SERIES

Description:
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate
Ball: 100Cr6 Heat Treated, polished and electroless Nickel plated and stainless steel 440C
Liner: High Strength PTFE Composite

Features:
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to +240°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specifications:
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-M14		14	M14x2.00	19	13.50	36	57	25	22	57000

Interchange table

Dunlop	Aurora	Fluro
FSX-M (Metric)	AW-M-T and AD-M-T	GUSW
FSX (Imperial)	AW-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060559883
Inside diameter	14 mm
Outside diameter	36 mm
Thickness	19 mm
Type	SI
Thread	Right-hand thread
Lubrication	NA
Static load	57 kN
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE