

Cam follower KR5204-2RS-INA - KR5204-2RS-INA

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/kr5204-2rs-ina>



D	52 mm
d	20 mm Tolérance : h7
B	63.6 mm
B _{1 max}	22.5 mm
B ₂	41.5 mm
C	20.6 mm
C ₁	1.5 mm
d ₂	26.8 mm
G	M20X1.5
l ₀	21 mm
R	500 mm Rayon du bombé
r _{max}	0.1 mm
W	10 mm Côte nominale du six pans creux
m	0.38 kg masse
M	160 Nm Couple de serrage de l'écrou
C _{dyn}	16100 N charge dyn. de base effective en tant que galet (radiale)
C _{stat}	10700 N charge stat. de base effective en tant que galet (radiale)
F _{0.2}	550 N charge limite à la fatigue
n _{0.2}	5000 1/min vitesse de rotation (en continu et pour lubrif. à la graisse)

PRODUCT FEATURES

Brand	INA
N° Ean13	3663952091358
Inside diameter	20 mm
Outside diameter	52 mm
Thickness	63.6 mm
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE