


Tapered roller bearing NN3014-K-NTN - NN3014-K-NTN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/nn3014-k-ntn>



Double Row Cylindrical Roller Bearing w/ Tapered Bore - Type NN - Dimensions

Technical Specifications		Operational Specifications	
Type	Cylindrical Roller Bearing	2.7558 in	70.000 mm
Bore Type	Tapered	4.3307 in	110.000 mm
Material	Hardened Alloy Steel	1.1811 in	30.000 mm
Cage Material	High Strength, 2 piece, hardened steel	1.1811 in	30.000 mm
Limiting Speed - Oil	6900 RPM	1.1811 in	30.000 mm
Limiting Speed - Grease	5800 RPM	3.9370 in	100.000 mm
Taper	1:12	r	0.0432 in
Precision	ABEC 3	da min	3.0118 in
Configuration	Open	da max	3.9764 in
Oil Hole	with Oil Hole	Db min	3.9764 in
Radial Internal Clearance	CN	Db max	4.0748 in
Static Load Rating	32000 lbf 143000 N 143.00 kN	rsa max	0.0394 in
Dynamic Load Rating	31200 lbf 94500 N 94.50 kN		
Enclosure	Open		
Operating Temperature Range	-40 to 250 °F -40 to 120 °C		

PRODUCT FEATURES

Brand	NTN
N° Ean13	3616060804792
Inside diameter	70 mm
Inside diameter	2.756" inch
Outside diameter	110 mm
Outside diameter	4.331" inch
Thickness	30 mm
Thickness	1.181" inch
Dynamic load	94.5 kN
Static load	143 kN
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE