

## Gasket sealer 5207-250ML-LOCTITE - 5207-250ML-LOCTITE

<https://www.123bearing.co.uk/lubricant-adhesive/adhesive/gasketsealer/5207-250ml-loctite>

<b>TITRE</b>	Anaérobie
<b>DESCRIPTION</b>	Étanchéité plane, moyennement flexible
<b>NOM</b>	LOCTITE 5207
<b>CONDITIONNEMENT</b>	Tube 250 ml
<b>COMMENTAIRE</b>	
<b>APPROBATION*</b>	

**Description**

LOCTITE® 5207 is a red, fluorescent, medium strength, medium viscosity, anaerobic sealant typically used as a form-in-place gasket on rigid flanged connections, e.g. gearbox and engine casings, etc. It seals close fitting joints between rigid metal faces and flanges and provides resistance to low pressures immediately after assembly of flanges.

**Avantages**

Fluorescent  
Medium strength  
Medium viscosity  
Provides resistance to low pressures immediately after assembly of flanges  
Maintains flexibility after exposure to high temperatures

**Caractéristiques**

Fluorescent dimethacrylate ester acrylic sealant used as a form-in-place gasket on rigid flanged connections, e.g. gearbox and engine casings, etc.

### PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	3616060812186
Weight	250 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE