

Glue

589-250ML-LOCTITE - 589-250ML-LOCTITE

<https://www.123bearing.co.uk/lubricant-adhesive/lubricant/glue/589-250ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Poréotanche, résistance élevée
NOM	LOCTITE 589
CONDITIONNEMENT	Facon 250 ml
COMMENTAIRE	
APPROBATION*	

Description

LOCTITE® 589 is a green, low-viscosity, dimethacrylate ester, acrylic, threadlocking adhesive. The product is used to lock and seal fine-threaded nuts, bolts and studs in a wide variety of applications. LOCTITE 589 is also used to seal porosity in welds, castings and powdered metal parts. Demonstrates high-strength capability.

Avantages

Ideal for fine-threaded nuts, bolts and studs
 Suits a wide variety of applications
 Also seals porosity in welds, castings and powdered metal parts
 Positive fluorescence under UV light

Caractéristiques

Acrylic green threadlocker with high strength. Used on fine-threaded nuts, bolts and studs.

PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	5010266589657
Type	ETANCHEITE
Weight	200 g
Packaging	1
Use	Anaérobie

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE