

Glue

680-250ML-LOCTITE - 680-250ML-LOCTITE

<https://www.123bearing.co.uk/lubricant-adhesive/lubricant/glue/680-250ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Viscosité moyenne, haute résistance
NOM	LOCTITE 680
CONDITIONNEMENT	11,250 ml
APPROBATION*	

Description

LOCTITE 680 is a green, high strength, methacrylate ester acrylic liquid designed for the bonding of cylindrical fitting parts, particularly where low viscosity is required. The product prevents loosening and leakage from shock and vibration. It provides robust curing performance. It works on active metals (e.g. mild steel) and on passive substrates (e.g. stainless steel and plated surfaces).

Avantages

Low viscosity provides outstanding performance. Cures when applied in the absence of air between close fitting parts. Offers high temperature performance and oil tolerance. Meets NSF H1 standard for use in commercial and residential potable water systems not exceeding +175.0 °F (+75 °C).

Caractéristiques

High strength, methacrylate ester acrylic liquid designed for the bonding of cylindrical fitting parts, particularly where low viscosity is required.



PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	5010266011165
Type	FIXATION ROULEMENT
Weight	325 g
Packaging	1
Use	Anaérobie

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE