



## Roller bearing NUP207-ECJ-SKF - NUP207-ECJ-SKF

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nup207-ecj-skf>

Dimensione																									
	<table border="0"> <tr><td>d</td><td>35</td><td>mm</td></tr> <tr><td>D</td><td>72</td><td>mm</td></tr> <tr><td>B</td><td>17</td><td>mm</td></tr> <tr><td>d<sub>1</sub></td><td>48.1</td><td>mm</td></tr> <tr><td>D<sub>1</sub></td><td>60.33</td><td>mm</td></tr> <tr><td>F</td><td>44</td><td>mm</td></tr> <tr><td>r<sub>1,2</sub></td><td>min. 1.1</td><td>mm</td></tr> <tr><td>r<sub>3,4</sub></td><td>max. 0.8</td><td>mm</td></tr> </table>	d	35	mm	D	72	mm	B	17	mm	d <sub>1</sub>	48.1	mm	D <sub>1</sub>	60.33	mm	F	44	mm	r <sub>1,2</sub>	min. 1.1	mm	r <sub>3,4</sub>	max. 0.8	mm
d	35	mm																							
D	72	mm																							
B	17	mm																							
d <sub>1</sub>	48.1	mm																							
D <sub>1</sub>	60.33	mm																							
F	44	mm																							
r <sub>1,2</sub>	min. 1.1	mm																							
r <sub>3,4</sub>	max. 0.8	mm																							
Dimensione d'appui																									
	<table border="0"> <tr><td>r<sub>1</sub></td><td>max. 41.8</td><td>mm</td></tr> <tr><td>r<sub>2</sub></td><td>min. 50</td><td>mm</td></tr> <tr><td>D<sub>2</sub></td><td>max. 65.1</td><td>mm</td></tr> <tr><td>r<sub>3</sub></td><td>max. 1</td><td>mm</td></tr> </table>	r <sub>1</sub>	max. 41.8	mm	r <sub>2</sub>	min. 50	mm	D <sub>2</sub>	max. 65.1	mm	r <sub>3</sub>	max. 1	mm												
r <sub>1</sub>	max. 41.8	mm																							
r <sub>2</sub>	min. 50	mm																							
D <sub>2</sub>	max. 65.1	mm																							
r <sub>3</sub>	max. 1	mm																							
Données de calcul																									
Charge dynamique de base	C	56	kN																						
Charge statique de base	C <sub>0</sub>	48	kN																						
Limite de fatigue	P <sub>e</sub>	6.1	kN																						
Vitesse de référence		11000	tr/min																						
Vitesse limite		12000	tr/min																						
Coefficient de calcul	k <sub>2</sub>	0.15																							
Calculations data																									
Calcul de la charge : Valeur limite	e	0.2																							
Calcul de la charge : Coefficient de calcul	Y	0.8																							
Masse																									
Masse du roulement		0.32	kg																						

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577034779
Inside diameter	35 mm
Outside diameter	72 mm
Thickness	17 mm
Dynamic load	56 kN
Static load	48 kN
Packaging	-

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE