


Housed bearing 2 bolts P2BC-35M-CPSS-DFH-SKF - P2BC-35M-CPSS-DFH-SKF

<https://www.123bearing.co.uk/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/p2bc-35m-cpss-dfh-skf>

Données de calcul																																																										
Charge dynamique de base	C ₀ 21.8 kN																																																									
Charge statique de base	C ₀ 15.3 kN																																																									
Limite de fatigue	F ₀ 0.655 kN																																																									
Compliance with standard	Not standardized																																																									
Matériau	Compatible for the SKF Food Line																																																									
Sealing solution	Gutter seals																																																									
Dimensions																																																										
	<table border="1"> <tr><td>d</td><td>35</td><td>mm</td></tr> <tr><td>A</td><td>40</td><td>mm</td></tr> <tr><td>A₁</td><td>40</td><td>mm</td></tr> <tr><td>B</td><td>68.6</td><td>mm</td></tr> <tr><td>B₁</td><td>34.9</td><td>mm</td></tr> <tr><td>C</td><td>6</td><td>mm</td></tr> <tr><td>D</td><td>69.8</td><td>mm</td></tr> <tr><td>H</td><td>47.6</td><td>mm</td></tr> <tr><td>H₁</td><td>26</td><td>mm</td></tr> <tr><td>J</td><td>127</td><td>mm</td></tr> <tr><td>J₁</td><td>max. 130</td><td>mm</td></tr> <tr><td>J₂</td><td>min. 124</td><td>mm</td></tr> <tr><td>L</td><td>168</td><td>mm</td></tr> <tr><td>N₁</td><td>17</td><td>mm</td></tr> <tr><td>N₂</td><td>14</td><td>mm</td></tr> <tr><td>P₁</td><td>25.4</td><td>mm</td></tr> <tr><td colspan="3">Photo de montage</td></tr> <tr><td>G</td><td>12</td><td>mm</td></tr> <tr><td>G₁</td><td>0.5</td><td>in</td></tr> </table>	d	35	mm	A	40	mm	A ₁	40	mm	B	68.6	mm	B ₁	34.9	mm	C	6	mm	D	69.8	mm	H	47.6	mm	H ₁	26	mm	J	127	mm	J ₁	max. 130	mm	J ₂	min. 124	mm	L	168	mm	N ₁	17	mm	N ₂	14	mm	P ₁	25.4	mm	Photo de montage			G	12	mm	G ₁	0.5	in
d	35	mm																																																								
A	40	mm																																																								
A ₁	40	mm																																																								
B	68.6	mm																																																								
B ₁	34.9	mm																																																								
C	6	mm																																																								
D	69.8	mm																																																								
H	47.6	mm																																																								
H ₁	26	mm																																																								
J	127	mm																																																								
J ₁	max. 130	mm																																																								
J ₂	min. 124	mm																																																								
L	168	mm																																																								
N ₁	17	mm																																																								
N ₂	14	mm																																																								
P ₁	25.4	mm																																																								
Photo de montage																																																										
G	12	mm																																																								
G ₁	0.5	in																																																								
Calculation data																																																										
Limiting speed	500 rpm																																																									
with shaft tolerance H6																																																										

PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577856005
Shaft diameter	35 mm
No. of fasteners	2
Tightening	Eccentric locking ring
Mounting center distance	127 mm
Material	FOOD-GRADE POLYPROPYLENE
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE