

## Housed bearing 2 bolts P2BC-35M-CPSS-DFH-SKF - P2BC-35M-CPSS-DFH-SKF

<https://www.123bearing.co.uk/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/p2bc-35m-cpss-dfh-skf>

|                          |                |                                 |       |    |
|--------------------------|----------------|---------------------------------|-------|----|
| <b>Données de calcul</b> |                |                                 |       |    |
| Charge dynamique de base | C              | 21.8                            | kN    |    |
| Charge statique de base  | C <sub>0</sub> | 15.3                            | kN    |    |
| Limite de fatigue        | F <sub>0</sub> | 0.655                           | kN    |    |
| Compliance with standard |                | Not standardized                |       |    |
| Matériau                 |                | Composite for the SKF Food Line |       |    |
| Sealing solution         |                | Gutter seals                    |       |    |
| <b>Dimensions</b>        |                |                                 |       |    |
|                          |                | d                               | 35    | mm |
|                          |                | A                               | 40    | mm |
|                          |                | A <sub>1</sub>                  | 40    | mm |
|                          |                | A <sub>2</sub>                  | 68.6  | mm |
|                          |                | B                               | 34.9  | mm |
|                          |                | B <sub>1</sub>                  | 6     | mm |
|                          |                | B <sub>2</sub>                  | 63.8  | mm |
|                          |                | H <sub>1</sub>                  | 47.6  | mm |
|                          |                | H <sub>2</sub>                  | 26    | mm |
|                          |                | J                               | 127   | mm |
|                          |                | J <sub>max</sub>                | 130   | mm |
|                          |                | J <sub>min</sub>                | 124   | mm |
|                          |                | L                               | 168   | mm |
|                          |                | N                               | 17    | mm |
|                          |                | N <sub>1</sub>                  | 14    | mm |
| P <sub>1</sub>           | 25.4           | mm                              |       |    |
| <b>Photo de serrage</b>  |                |                                 |       |    |
| G                        | 12             | mm                              |       |    |
| G                        | 0.5            | in                              |       |    |
| <b>Calculation data</b>  |                |                                 |       |    |
| Limiting speed           |                | 300                             | 1/min |    |
| with shaft tolerance H6  |                |                                 |       |    |

### PRODUCT FEATURES

|                          |                          |
|--------------------------|--------------------------|
| Brand                    | SKF                      |
| N° Ean13                 | 7316577856005            |
| Shaft diameter           | 35 mm                    |
| No. of fasteners         | 2                        |
| Tightening               | Eccentric locking ring   |
| Mounting center distance | 127 mm                   |
| Material                 | FOOD-GRADE POLYPROPYLENE |
| Packaging                | 1                        |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE