

Tapered roller bearing 30226-JR-JTEKT - 30226-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30226-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
130	230	43.75	40	34	3	377	511	1 600	2 100	30226JR				
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
4FB	46.2	148	152	216	203	218	7	9.5	3	2.5	0.44	1.38	0.76	7.24

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250121586
Inside diameter	130 mm
Outside diameter	230 mm
Thickness	43.75 mm
Weight	7135 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE