

Tapered roller bearing 938-932-JTEKT - 938-932-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/938-932-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_2 max.	C_r	C_{10}	Grease lub.	Oil lub.
114.300	212.725	66.675	66.675	53.975	7.1	3.2	450	674	1 800	2 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
938	932	47.6	141.0	128.0	187.0	193.0	7.1	3.2	0.33	1.84	1.01	5.96	4.07

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250209734
Inside diameter	114.3 mm
Outside diameter	212.72 mm
Thickness	53.9 mm
2nd Thickness	66.6 mm
Packaging	-

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE