

Tapered roller bearing 322-22-R-JTEKT - 322-22-R-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/322-22-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C _{0r}	C _{0r}	Grease lub.	Oil lub.				
22	50	19.25	18	15	1	1	36.8	41.6	8 100	11 000	322/22R			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S ₁ min.	S ₂ min.	r ₁ max.	r ₂ max.		Y ₁	Y ₀		
—	14.0	27.5	29	44.5	41	46	2	4	1	1	0.37	1.00	0.88	0.178

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952400433
Inside diameter	22 mm
Outside diameter	50 mm
Thickness	19.25 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE