

## Tapered roller bearing 32909-JR-JTEKT - 32909-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32909-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
45	68	15	15	12	0.6	0.6	34.7	52.4	5 300	7 100	32909JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
29C	12.5	49.5	50	63.5	61	64	3	3	0.6	0.6	0.32	1.88	1.04	0.190

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952404974
Inside diameter	45 mm
Outside diameter	68 mm
Thickness	15 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE