

## Tapered roller bearing T2EE060-JTEKT - T2EE060-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/t2ee060-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
60	115	40	39	33	2.5	2.5	183	242	3 400	4 600	T2EE060			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2EE	27.6	72	70	103	98	109	6	7	2	2	0.33	1.80	0.99	1.80

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952406022
Inside diameter	60 mm
Outside diameter	115 mm
Thickness	40 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE