

## Tapered roller bearing 30316-JR-JTEKT - 30316-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30316-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
80	170	42.5	39	33	3	2.5	294	355	2 300	3 100	<b>30316JR</b>			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>a</sub> min.	d <sub>a</sub> max.	D <sub>a</sub> min.	D <sub>a</sub> max.	S <sub>a</sub> min.	S <sub>a</sub> max.	r <sub>a</sub> min.	r <sub>a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2GB	34.8	94	102	158	148	159	4	9.5	2.5	2	0.35	1.74	0.96	4.46

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122224
Inside diameter	80 mm
Outside diameter	170 mm
Thickness	42.5 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE