


Tapered roller bearing 32316-JR-JTEKT - 32316-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32316-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
80	170	61.5	58	48	3	2.5	383	503	2 300	3 100	32316JR			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
260	43.5	94	98	158	142	159	4	13.5	2.5	2	0.35	1.74	0.96	6.31

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125195
Inside diameter	80 mm
Outside diameter	170 mm
Thickness	61.5 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE