


Tapered roller bearing T2ED080-JTEKT - T2ED080-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/t2ed080-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
80	145	46	45	38	3	2.5	266	381	2 600	3 500	T2ED080			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
2ED	32.7	94	92	133	125	137	7	8	2.5	2	0.32	1.88	1.03	3.20

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409566
Inside diameter	80 mm
Outside diameter	145 mm
Thickness	46 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE