

Tapered roller bearing 32318-JR-JTEKT - 32318-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32318-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
90	190	67.5	64	53	461	614			2 100	2 800	32318JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
260	46.6	108	108	176	157	177	5	14.5	3	2.5	0.35	1.74	0.96	8.61

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125249
Inside diameter	90 mm
Outside diameter	190 mm
Thickness	67.5 mm
Weight	8061 g
Packaging	-

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE