

Tapered roller bearing 33219-JR-JTEKT - 33219-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/33219-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
95	170	58	58	44	3	2.5	374	582	2 200	2 900	33219JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S ₁ min.	S ₂ min.	r ₃ min.	r ₄ max.		Y ₁	Y ₀		
3FE	42.8	109	107	158	144	163	9	14	2.5	2	0.41	1.47	0.81	5.66

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409788
Inside diameter	95 mm
Outside diameter	170 mm
Thickness	58 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE