

Tapered roller bearing 30319-DJR-JTEKT - 30319-DJR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30319-djr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|-------------------------------|---------------------------|----------------|------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | |
| 95 | 200 | 49.5 | 45 | 32 | 319 | 391 | 1 700 | 2 300 | 30319DJR | | | | |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | Constant e | Axial load factors (Refer. 1) | | Mass (kg) | | |
| 7GB | 62.7 | d _{1a} min. | d _{2a} max. | D _{1a} max. | D _{2a} min. | S _{1a} min. | S _{2a} min. | r _{1a} max. | r _{2a} max. | Y ₁ | Y ₀ | 6.68 | |
| | | 113 | 113 | 186 | 157 | 187 | 6 | 17.5 | 3 | 2.5 | 0.83 | 0.73 | 0.40 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250122378 |
| Inside diameter | 95 mm |
| Outside diameter | 200 mm |
| Thickness | 49.5 mm |
| Packaging | - |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE