

## Tapered roller bearing 30319-JR-JTEKT - 30319-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30319-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>						
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.		Oil lub.					
95	200	49.5	45	38	4	3	372	455	2 000	2 600	30319JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
20B	40.8	113	118	186	172	186	5	11.5	3	2.5	0.35	1.74	0.96	6.96

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409818
Inside diameter	95 mm
Inside diameter	3.74" inch
Outside diameter	200 mm
Outside diameter	7.874" inch
Thickness	49.5 mm
Thickness	1.949" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE