

Tapered roller bearing 32220-JR-JTEKT - 32220-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32220-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
100	180	49	46	39	3	2.5	347	495	2 100	2 800	32220JR			
Dimension series to ISO995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
3FG	42.1	114	114	168	154	171	5	10	2.5	2	0.42	1.43	0.79	5.21

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250124679
Inside diameter	100 mm
Inside diameter	3.937" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	49 mm
Thickness	1.929" inch
Weight	4900 g
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE