

Tapered roller bearing 30321-JR-JTEKT - 30321-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30321-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
105	225	53.5	49	41	464	578	1700	2300			30321JR			
Dimension series to ISO355 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2GB	44.1	123	132	211	193	209	7	12.5	3	2.5	0.35	1.74	0.96	9.73

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952410715
Inside diameter	105 mm
Outside diameter	225 mm
Thickness	53.5 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE