

Tapered roller bearing 32222-JR-JTEKT - 32222-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32222-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
110	200	56	53	46	3	2.5	438	640	1 900	2 500	32222JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
3FG	46.7	124	126	188	170	190	6	10	2.5	2	0.42	1.43	0.79	7.45

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250124730
Inside diameter	110 mm
Outside diameter	200 mm
Thickness	56 mm
Weight	7154 g
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE