

Tapered roller bearing 30322-D-JTEKT - 30322-D-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30322-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
110	240	54.5	50	38	4	3	385	429	1 400	1 900	30322D			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{3a} min.	r _{3a} max.		Y ₁
—	71.5	128	135	226	205	222	6	18	3	2.5	0.81	0.74	0.41	10.2

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122460
Inside diameter	110 mm
Outside diameter	240 mm
Thickness	54.5 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE