

## Tapered roller bearing 32322-JR-JTEKT - 32322-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32322-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>						
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.		Oil lub.					
110	240	84.5	80	65	691	943	1 600	2 200	<b>32322JR</b>					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.		r <sub>1</sub> max.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
260	59.3	128	137	226	198	222	9	19.5	3	2.5	0.35	1.74	0.96	17.8

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411330
Inside diameter	110 mm
Inside diameter	4.331" inch
Outside diameter	240 mm
Outside diameter	9.449" inch
Thickness	84.5 mm
Thickness	3.327" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE