

Tapered roller bearing 33024-JR-JTEKT - 33024-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/33024-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.		
120	180	48	48	38	299	540	2 000	2 600	33024JR	

Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2DE	36.2	132	132	170	160	171	6	10	2	2	0.31	1.97	1.08	4.16

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126079
Inside diameter	120 mm
Outside diameter	180 mm
Thickness	48 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE