

Tapered roller bearing 30324-D-JTEKT - 30324-D-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30324-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
120	260	59.5	55	38	430	512			1 200	1 700	30324D			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	77.8	138	145	246	219	239	6	21	3	2.5	0.81	0.74	0.41	13.0

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122507
Inside diameter	120 mm
Outside diameter	260 mm
Thickness	59.5 mm
Weight	13000 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE