

Tapered roller bearing 32324-JR-JTEKT - 32324-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32324-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
120	260	90.5	86	69	4	3	800	1 110	1 500	2 000	32324JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
260	62.7	138	148	246	213	239	9	21.5	3	2.5	0.35	1.74	0.96	22.2

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125355
Inside diameter	120 mm
Outside diameter	260 mm
Thickness	90.5 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE