

Tapered roller bearing 32956-JR-JTEKT - 32956-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32956-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.							
280	380	63.5	63.5	48	780	1630	770	1000	32956JR						
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{2a} min.	r _{2a} max.		Y ₁	Y ₀	
4EC	75.1	294	298	368	347	368	11	15.5	2.5	2	0.43	1.39	0.76	20.14	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125812
Inside diameter	280 mm
Outside diameter	380 mm
Thickness	63.5 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE