

Tapered roller bearing 32964-JR-JTEKT - 32964-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32964-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾						
d	D	T	B	C	C _r	C _{0r}	Grease lub.		Oil lub.					
320	440	76	76	57	1 060	2 270	640	850	32964JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.	Constant e	Axial load factors (Refer. 1)		Mass (kg)	
3FD	85.0	338	342	426	401	426	12	19	3	2.5	0.42	1.44		0.79

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952412085
Inside diameter	320 mm
Outside diameter	440 mm
Thickness	76 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE