

## Tapered roller bearing 30264-JTEKT - 30264-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30264-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
320	580	104	92	75	5	1740	2770	490	660	30264				
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	111.9	348	370	558	505	540	14	28	5	4	0.42	1.44	0.79	108

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952412108
Inside diameter	320 mm
Outside diameter	580 mm
Thickness	104 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE