

## Tapered roller bearing 30328-JR-JTEKT - 30328-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30328-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
140	300	67.75	62	53	749	962	1 300	1 700	30328JR				
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)							Constant e	Axial load factors (Refer. 1)		Mass (kg)	
2GB	56.9	d <sub>1a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> max.	D <sub>2a</sub> min.	S <sub>1a</sub> min.	S <sub>2a</sub> min.	r <sub>1a</sub> max.	r <sub>2a</sub> max.	0.35	Y <sub>1</sub> 1.74	Y <sub>0</sub> 0.96	22.6

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419824
Inside diameter	140 mm
Inside diameter	5.512" inch
Outside diameter	300 mm
Outside diameter	11.811" inch
Thickness	67.75 mm
Thickness	2.667" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE