

## Tapered roller bearing 32328-R-JTEKT - 32328-R-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32328-r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>						
d	D	T	B	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.							
140	300	107.75	102	85	5	4	1 110	1 570	1 300	1 700	32328R			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	74.2	162	175	282	246	280	10	17	4	3	0.35	1.74	0.96	35.1

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419848
Inside diameter	140 mm
Outside diameter	300 mm
Thickness	107.75 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE