

Tapered roller bearing 30230-JR-JTEKT - 30230-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30230-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
150	270	49	45	38	483	664	1 300	1 800	30230JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4GB	52.4	168	175	256	234	255	9	11	3	2.5	0.44	1.38	0.76	11.6

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250258749
Inside diameter	150 mm
Outside diameter	270 mm
Thickness	49 mm
Weight	10500 g
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE