

Tapered roller bearing 30330-JR-JTEKT - 30330-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30330-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
150	320	72	65	55	837	1080	1200	1500	30330JR					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
26B	60.8	172	193	302	272	292	12	17	4	3	0.35	1.74	0.96	26.6

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419916
Inside diameter	150 mm
Outside diameter	320 mm
Thickness	72 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE