

Tapered roller bearing 32932-JR-JTEKT - 32932-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32932-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo

TECHNICAL DATA

Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No.
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₂ max.	<i>C</i> _r	<i>C</i> _{0r}	Grease lub.	Oil lub.	
160	220	38	38	30	2.5	2	295	568	1 500	2 000	32932JR

Dimension series to ISO 955 (Refer. 1)	Load center (mm) <i>a</i>	Mounting dimensions (mm)										Constant <i>e</i>	Axial load factors		(Refer. 1) Mass (kg)
		<i>d</i> _a min.	<i>d</i> _a max.	<i>D</i> _a min.	<i>D</i> _a max.	<i>S</i> _a min.	<i>S</i> _a max.	<i>r</i> _a min.	<i>r</i> _a max.	<i>r</i> _b min.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₀	
2DC	38.4	172	173	210	204	212	7	8	2	2	2	0.35	1.73	0.95	4.19

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125713
Inside diameter	160 mm
Outside diameter	220 mm
Thickness	38 mm
Weight	4190 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE