

Tapered roller bearing 32032-JR-JTEKT - 32032-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32032-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
160	240	51	51	38	3	2.5	440	758	1 400	1 900	32032JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4EC	52.1	174	175	228	213	231	8	13	2.5	2	0.46	1.31	0.72	7.75

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421230
Inside diameter	160 mm
Outside diameter	240 mm
Thickness	51 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE