

Tapered roller bearing 32034-JR-JTEKT - 32034-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32034-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 170 | 260 | 57 | 57 | 43 | 526 | 905 | 1 300 | 1 700 | 32034JR | | | | | |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 4EC | 55.8 | 184 | 187 | 248 | 230 | 249 | 10 | 14 | 2.5 | 2 | 0.44 | 1.35 | 0.74 | 10.5 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250123726 |
| Inside diameter | 170 mm |
| Outside diameter | 260 mm |
| Thickness | 57 mm |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE