

## Tapered roller bearing 30334-D-JTEKT - 30334-D-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30334-d-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
170	360	80	72	50	782	1040	830	1200	30334D					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	108.3	192	211	342	310	333	9	30	4	3	0.81	0.74	0.41	34.3

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421339
Inside diameter	170 mm
Outside diameter	360 mm
Thickness	80 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE