

Tapered roller bearing 32334-JTEKT - 32334-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32334-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
170	360	127	120	100	1310	1830	1000	1300	32334					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	86.1	192	200	342	295	337	14	26	4	3	0.35	1.73	0.95	56.9

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421353
Inside diameter	170 mm
Outside diameter	360 mm
Thickness	127 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE