

Tapered roller bearing 30236-JR-JTEKT - 30236-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30236-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|--------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 180 | 320 | 57 | 52 | 43 | 615 | 870 | 1 100 | 1 400 | 30236JR | | | | | |
| Dimension series to ISO 995 (Refer.) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer.) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 4GB | 63.6 | 202 | 211 | 302 | 278 | 297 | 9 | 14 | 4 | 3 | 0.45 | 1.33 | 0.73 | 18.3 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952421384 |
| Inside diameter | 180 mm |
| Inside diameter | 7.087" inch |
| Outside diameter | 320 mm |
| Outside diameter | 12.598" inch |
| Thickness | 57 mm |
| Thickness | 2.244" inch |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE