

Tapered roller bearing 32938-JR-JTEKT - 32938-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32938-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
190	260	45	45	34	366	789	1 200	1 600	32938JR					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4DC	55.0	202	204	250	235	252	8	11	2	2	0.48	1.26	0.69	6.89

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125751
Inside diameter	190 mm
Outside diameter	260 mm
Thickness	45 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE