

Tapered roller bearing 30240-JR-JTEKT - 30240-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30240-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C _{0e}	C _{0a}	Grease lub.	Oil lub.	
200	360	64	58	48	792	1120			940	1200	30240JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4GB	70.3	222	238	342	315	336	12	15	4	3	0.44	1.38	0.76	26.4

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250121654
Inside diameter	200 mm
Inside diameter	7.874" inch
Outside diameter	360 mm
Outside diameter	14.173" inch
Thickness	64 mm
Thickness	2.52" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE