

Tapered roller bearing 30340-D-JTEKT - 30340-D-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30340-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
200	420	89	80	56	904	1230	690	970			30340D

Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	122.6	228	248	398	365	385	11	33	5	4	0.81	0.74	0.41	50.6

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421612
Inside diameter	200 mm
Outside diameter	420 mm
Thickness	89 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE