

## Tapered roller bearing 32944-JR-JTEKT - 32944-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32944-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
220	300	51	51	39	498	1010			1000	1400	32944JR

  

Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	r <sub>2a</sub> min.	r <sub>2a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
3EC	58.6	234	234	288	275	290	9	12	2.5	2	0.43	1.41	0.78	10.1	

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125799
Inside diameter	220 mm
Outside diameter	300 mm
Thickness	51 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE