

## Tapered roller bearing 32044-JR-JTEKT - 32044-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32044-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>0r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
220	340	76	76	57	894	1620	940	1300			32044JR				
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>3a</sub> min.	r <sub>3a</sub> max.	Y <sub>1</sub>	Y <sub>0</sub>				
4FD	72.8	238	243	326	300	326	12	19	3	2.5	0.43	1.39	0.77	25.2	

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250123788
Inside diameter	220 mm
Outside diameter	340 mm
Thickness	76 mm
Packaging	-

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE