

Tapered roller bearing 30244-JR-JTEKT - 30244-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30244-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.					
220	400	72	65	54	1010	1440	830	1100			30244JR				
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀	
—	76.5	242	263	382	344	371	14	17	4	3	0.44	1.43	0.79	35.9	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421674
Inside diameter	220 mm
Outside diameter	400 mm
Thickness	72 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE