

Tapered roller bearing 32048-JR-JTEKT - 32048-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32048-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|---------------------------------------|--------------------|--------------------------|----------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | | | | |
| 240 | 360 | 76 | 76 | 57 | 924 | 1720 | 870 | 1200 | | | 32048JR | | | |
| Dimension series to ISO355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 4FD | 78.5 | 258 | 261 | 346 | 318 | 346 | 12 | 19 | 3 | 2.5 | 0.46 | 1.31 | 0.72 | 26.8 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250123795 |
| Inside diameter | 240 mm |
| Outside diameter | 360 mm |
| Thickness | 76 mm |
| Packaging | - |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE